

Appl. No. «10/660,873 »
Amtdt dated September 15, 2006

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

Claims 1-32 (canceled).

Claim 33 (currently amended): A method according to claim ~~[[1,]]~~ 34 further comprising:

writing the data to the storage medium with a grain diameter below 100 Å.

Claim 34 (currently amended): ~~A method according to claim 1, further comprising~~

A method for storing data on a storage medium comprising a magnetic disk, the method comprising:

writing the data to the storage medium in which the spacing between adjacent magnetized locations of the magnetic disk is smaller than 50nm whereby the data for a recording density is written at greater than 500 kFCI (19685 kFCm) so as to cause spontaneous degradation of the data over time;

automatically reading the data periodically;

generating a refresh indicator and checking if the refresh indicator satisfies a predetermined condition related to degradation of the data over time; and

writing the data a second time at least in response to said predetermined condition being satisfied;

wherein writing the data is written to the storage medium with an energy ratio below 50 KuV/KBT at room temperature.

SILICON VALLEY
PATENT GROUP LLP
2150 Mission College Blvd
Suite 360
Santa Clara, CA 95054
(408) 982-8200
FAX (408) 982-8210

Appl. No. «10/660,873 »
Amdt dated September 15, 2006

Claim 35 (currently amended): A method according to ~~any one of claims 1, 33 and claim 34~~ further comprising estimating an expected time to occurrence of a hard error by any one or more of the steps of (a) checking if the readback signal has fallen to at least 88% of its original amplitude, (b) empirically determining the duration of operation without errors on a test disk, and using this error free duration to generate and store a refresh date, (c) determining the occurrence of a predetermined number of soft errors.

Claim 36 (currently amended): A method according to ~~any one of claims 1, 33 and claim 34, the method further comprising: writing the data to the magnetic disk, wherein:~~

at least a portion of the data ~~being~~ is written to a group of grains in a track of the magnetic disk at a density sufficiently high to cause a change in direction of magnetization of at least some of the grains with passage of said time; and

~~automatically refreshing at least the portion of data, using the refresh indicator.~~

Claim 37 (previously presented): A method according to claim 36 comprising automatically refreshing at least the portion of data, using at least two refresh indicators.

Claim 38 (currently amended): The method of ~~any one of claims 1, 33 and claim 34~~ further comprising writing the refresh indicator to a location in the storage medium distinct from another location used to write data.

Claim 39 (previously presented): The method of claim 38 further comprising using a date of performance of said "writing the data to the storage medium" to determine the refresh indicator.

Appl. No. «10/660,873 »
Amdt dated September 15, 2006

Claim 40 (previously presented): The method of claim 39 wherein:

said using includes setting the refresh indicator to be said date; and

said predetermined condition is satisfied when said refresh indicator is older than a current date by a predetermined time period.

Claim 41 (previously presented): The method of claim 39 wherein:

said determining includes setting the refresh indicator to be a refresh date obtained by adding a predetermined time period to said date; and

said predetermined condition is satisfied when said refresh date is older than a current date.

Claim 42 (currently amended): The method of ~~any one of claims 1, 33 and~~ claim 34 further comprising:

determining, subsequent to said writing, a difference between a first value of the refresh indicator determined contemporaneous with said writing and a second value of the refresh indicator determined at a current time;

wherein said predetermined condition is satisfied when said difference is greater than a predetermined limit.

Claim 43 (currently amended): The method of any one of claims ~~1, 33 and~~ 34 further comprising using an amplitude of a readback signal of the data as the refresh indicator.

SILICON VALLEY
PATENT GROUP LLP
2350 Mission College Blvd
Suite 363
Santa Clara, CA 95054
(408) 982-4200
FAX (408) 982-8210

Appl. No. «10/660,873 »
Amdt dated September 15, 2006

Claim 44 (previously presented): The method of claim 43 wherein said amplitude is hereinafter "first amplitude" and the method further comprises:

writing the first amplitude to a location in the storage medium distinct from another location used to write the data;

measuring a second amplitude of the readback signal contemporaneous with said checking; and

said checking includes determining a difference between the second amplitude and the first amplitude.

Claim 45 (previously presented): The method of claim 44 wherein said checking further comprises comparing said difference with a predetermined limit.

Claim 46 (previously presented): The method of claim 45 wherein said checking further comprises comparing a percentage value of said difference with a predetermined percentage.

Claim 47 (currently amended): The method of ~~claims 1, 33 and~~ claim 34 wherein the checking is performed periodically without scanning the entire storage medium.

Claim 48 (currently amended): The method of ~~claims 1, 33 and~~ claim 34 wherein the refresh indicator is saved contemporaneous with said writing.

SILICON VALLEY
PATENT GROUP LLP
3250 Mission College Blvd
Suite 360
San Jose, CA 95054
(408) 982-8200
FAX (408) 982-8210

Appl. No. «10/660,873 »
Amdt dated September 15, 2006

Claim 49 (currently amended): The method of ~~claims 1, 33 and~~ claim 34 wherein said "automatically reading the data" and said "writing the data a second time" are both performed periodically.

Claim 50 (currently amended): The method of ~~claims 1, 33 and~~ claim 34 wherein said "automatically reading the data" and said "writing the data a second time" are both performed on a schedule for all the data.

Claim 51 (previously presented): The method of claim 50 wherein said schedule is periodic.

Claim 52 (canceled).

Claim 53 (currently amended): ~~The storage medium of claim 52~~ A storage medium comprising:

a disk carrying data and having at least one property selected from a group of properties consisting of (a) spacing between adjacent magnetised locations of the magnetic disk less than 50 nm (b) recording density for data greater than 500 kFCI (19685 kFCm) (c) grain diameter less than 100 Å and (d) energy ratio less than 50 KuV/KBT so as to cause spontaneous degradation over time;

wherein the disk carries a refresh indicator that indicates a predetermined condition related to degradation of the data over time;

wherein~~[[;]]~~ the data is held ~~[[on]]~~ in a file~~[[;]]~~ and the refresh indicator is stored as an attribute of the file.

Appl. No. «10/660,873 »
Amdt dated September 15, 2006

Claim 54 (currently amended): The storage medium of ~~claim 52 or~~ claim 53 wherein the attribute is stored in a directory entry of a file system.

Claim 55 (currently amended): The storage medium of ~~claim 52 or~~ claim 53 wherein the refresh indicator is based on a time when the data were most recently written.

Claim 56 (currently amended): The storage medium of ~~any one of claims 52 and~~ claim 53 wherein the refresh indicator is based on an amplitude of a readback signal of the data at the time of writing the data.

Claim 57 (currently amended): The storage medium of ~~any one of claims 52 and~~ claim 53 wherein the data is held as polarity of magnetized portion of the storage medium.

Claims 58-70 (canceled).

Claim 71 (previously presented): A method for storing information on a magnetic disk, the method comprising:

writing the information to the magnetic disk, at least a portion of the information being written to a group of grains in a track at a density sufficiently high to cause a change in direction of magnetization of at least some of the grains with passage of a year; and automatically refreshing at least the portion of information, using a refresh indicator;

wherein a transition in polarity between neighboring magnetized portions is less than 250 Å.

Claims 72-76 (canceled).

Appl. No. «10/660,873 »
Amdt dated September 15, 2006

Claim 77 (previously presented): A method for storing information on a magnetic disk, the method comprising:

writing the information to the magnetic disk, at least a portion of the information being written to a group of grains in a track at a density sufficiently high to cause a change in direction of magnetization of at least some of the grains with passage of a year; and
automatically refreshing at least the portion of information, using a refresh indicator;

wherein said refresh indicator indicates that the information in the magnetic disk contains a soft error.

Claims 78-82 (canceled).

Claim 83 (previously presented): A method for storing information on a magnetic disk, the method comprising:

writing the information to the magnetic disk, at least a portion of the information being written to a group of grains in a track at a density sufficiently high to cause a change in direction of magnetization of at least some of the grains with passage of a year; and
automatically refreshing at least the portion of information, using at least two refresh indicators;

wherein at least one of the refresh indicators is related to a high-frequency component of a readback signal.

Claim 84 (previously presented): A method for storing information on a magnetic disk, the method comprising:

writing the information to the magnetic disk, at least a portion of the information being written to a group of grains in a track at a density sufficiently high to cause a change in direction of magnetization of at least some of the grains with passage of a year; and
automatically refreshing at least the portion of information, using at least two refresh indicators;

wherein at least one of the refresh indicators is related to a number of errors.

Appl. No. «10/660,873 »
Amdt dated September 15, 2006

Claim 85 (currently amended): ~~The method of Claim 1~~

A method for storing data on a storage medium comprising a magnetic disk, the method comprising:

writing the data to the storage medium in which the spacing between adjacent magnetized locations of the magnetic disk is smaller than 50nm whereby the data for a recording density is written at greater than 500 kFCI (19685 kFCm) so as to cause spontaneous degradation of the data over time;

automatically reading the data periodically;

generating a refresh indicator and checking if the refresh indicator satisfies a predetermined condition related to degradation of the data over time; and

writing the data a second time writing the data a second time at least in response to said predetermined condition being satisfied;

wherein[[:]] the refresh indicator is stored on the storage medium at a lower density than the data.

Claim 86 (previously presented): A method for storing information on a magnetic disk, the method comprising:

writing the information to the magnetic disk, at least a portion of the information being written to a group of grains in a track at a density sufficiently high to cause a change in direction of magnetization of at least some of the grains with passage of a year; and

automatically refreshing at least the portion of information, using a refresh indicator;

wherein the refresh indicator satisfies a predetermined condition; and

wherein the refresh indicator is stored on the magnetic disk at a lower density than the portion of the information.

Claim 87 (previously presented): The method of Claim 77 wherein:

the refresh indicator is stored on the magnetic disk at a lower density than the portion of the information.

Claim 88 (previously presented): The method of Claim 71 wherein:

Appl. No. «10/660,873 »
Amdt dated September 15, 2006

the refresh indicator is stored on the magnetic disk at a lower density than the portion of the information.

Claim 89 (currently amended): ~~The method of claim 70~~

A method for storing information on a magnetic disk, the method comprising:
writing the information to the magnetic disk, at least a portion of the information
being written to a group of grains in a track at a density sufficiently high to cause a change
in direction of magnetization of at least some of the grains with passage of a year; and
automatically refreshing at least the portion of information, using a refresh indicator;
wherein the diameter of at least one grain in the group of grains is less than 100
angstroms; and

wherein[[:]] the refresh indicator is stored on the magnetic disk at a lower density than the portion of the information.

Claim 90 (currently amended): ~~The storage medium of Claim 65~~ A storage
medium embedded with computer instructions comprising instructions for:

writing data to a magnetic medium wherein the spacing between adjacent
magnetised locations of the medium is smaller than 50 nm and the recording density is
greater than 500kFCI (19685 kFCm); and

automatically reading the data and writing the data back to the magnetic medium
without scanning the magnetic medium;

wherein during each writing the data are recorded at a density sufficiently high to
spontaneously undergo thermal degradation with passage of time;

wherein the computer instructions include checking if a refresh indicator satisfies a
predetermined condition related to degradation of the data over time;

wherein the computer instructions further comprise[[:]] storing the refresh indicator on the magnetic medium at a lower density than the data.

Claim 91 (currently amended): ~~The storage medium of Claim 52~~

A storage medium comprising:

SILICON VALLEY
PATENT GROUP LLP
2350 Mission College Blvd
Suite 300
Santa Clara, CA 95054
(408) 982-8200
FAX (408) 982-8210

Appl. No. «10/660,873 »
Amdt dated September 15, 2006

a disk carrying data and having at least one property selected from a group of properties consisting of (a) spacing between adjacent magnetised locations of the magnetic disk less than 50 nm (b) recording density for the data greater than 500 kFCI (19685 kFCm) (c) grain diameter less than 100 Å and (d) energy ratio less than 50 KuV/KBT so as to cause spontaneous degradation over time;

wherein the disk carries a refresh indicator that indicates a predetermined condition related to degradation of the data over time;

wherein the refresh indicator is carried on the disk at a lower density than the data.

Claim 92 (new): The method of claim 71 further comprising using an amplitude of a readback signal of the information as the refresh indicator.

Claim 93 (new): The method of claim 77 further comprising using an amplitude of a readback signal of the information as the refresh indicator.

Claim 94 (new): The method of claim 86 further comprising using an amplitude of a readback signal of the information as the refresh indicator.

Claim 95 (new): The method of claim 89 further comprising using an amplitude of a readback signal of the information as the refresh indicator.

Claim 96 (new): The storage medium of claim 53 wherein the disk carries the refresh indicator at a location distinct from another location carrying the data.

Claim 97 (new): The method of claim 71 further comprising writing the refresh indicator to a location in the magnetic disk distinct from another location used to write the portion of the information.

Claim 98 (new): The method of claim 77 further comprising writing the refresh indicator to a location in the magnetic disk distinct from another location used to write the portion of the information.

Appl. No. «10/660,873 »
Amdt dated September 15, 2006

Claim 99 (new): The method of claim 85 further comprising writing the refresh indicator to a location in the storage medium distinct from another location used to write data.

Claim 100 (new): The method of claim 86 further comprising writing the refresh indicator to a location in the magnetic disk distinct from another location used to write the portion of the information.

Claim 101 (new): The method of claim 83 further comprising writing at least one of the refresh indicators to a location in the magnetic disk distinct from another location used to write the portion of the information.

Claim 102 (new): The method of claim 84 further comprising writing at least one of the refresh indicators to a location in the magnetic disk distinct from another location used to write the portion of the information.

Claim 103 (new): The storage medium of claim 53 wherein the refresh indicator is stored in the disk at a lower density than the data.

Claim 104 (new): The method of claim 71 wherein the refresh indicator is based on a time when at least a portion of the information was most recently written.

Claim 105 (new): The method of claim 77 wherein the refresh indicator is based on a time when at least a portion of the information was most recently written.

Claim 106 (new): The method of claim 85 wherein the refresh indicator is based on a time when the data was most recently written.

Claim 107 (new): The method of claim 86 wherein the refresh indicator is based on a time when at least a portion of the information was most recently written.

Claim 108 (new): The method of claim 71 wherein the portion of the information is written to the magnetic disk with a grain diameter below 100 Å.

SILICON VALLEY
PATENT GROUP LLP
2350 Mission College Blvd
Suite 300
Santa Clara, CA 95054
(408) 982-8200
FAX (408) 982-8210

Appl. No. «10/660,873 »
Amdt dated September 15, 2006

Claim 109 (new): The method of claim 77 wherein the portion of the information is written to the magnetic disk with a grain diameter below 100 Å.

Claim 110 (new): The method of claim 83 wherein the portion of the information is written to the magnetic disk with a grain diameter below 100 Å.

Claim 111 (new): The method of claim 84 wherein the portion of the information is written to the magnetic disk with a grain diameter below 100 Å.

Claim 112 (new): The method of claim 85 wherein the data is written to the storage medium with a grain diameter below 100 Å.

Claim 113 (new): The method of claim 86 wherein the portion of the information is written to the magnetic disk with a grain diameter below 100 Å.

Claim 114 (new): The method of claim 89 wherein the portion of the information is written to the magnetic disk with a grain diameter below 100 Å.

Claim 115 (new): The storage medium of claim 90 wherein the data is written to the magnetic medium with a grain diameter below 100 Å.

Claim 116 (new): The method of claim 91 wherein the data is written to the disk with a grain diameter below 100 Å.

Claim 117 (new): The method of claim 85 further comprising using an amplitude of a readback signal of the data as the refresh indicator.

Claim 118 (new): The storage medium of claim 90 wherein an amplitude of a readback signal of the data is used as the refresh indicator by the computer instructions.

SILICON VALLEY
PATENT GROUP LLP

2350 Mission College Blvd
Suite 300
Santa Clara, CA 95054
(408) 982-8200
FAX (408) 982-8210